

M-JPEG/MPEG-4 IP Cameras

JNC-2413

1/3" Day/Night High-Res Color IP Camera

JNC-2413W

1/3" Day/Night High-Res Color Wireless IP Camera



Optional



POE Kit



Features

- MPEG4 / MJPEG Dual codec compression
- MPEG4 / MJPEG Dual streaming
- Up to D1 Resolution
- 2-way audio
- Support SD card for local record
- 3GPP for monitoring via 3G mobile phone
- IO: 2 in/ 2 out
- Support 802.11 b/g Wireless protocol (JNC-2413W)
- Removable IR Cut Filter (ICR, Optional)
- DC 12V
- Bundled with 36-Ch. Basic Version of Video Management Software (VMS)

Specification

Model	JNC-2413	JNC-2413W
CPU	ARM 9, 32 bit RISC	
RAM	64MB	
ROM	8MB	
Image Sensor	1/3" SONY CCD	
Lens	Fixed Lens, Focal length 6.0mm, F1.6	
Horizontal Resolution	520 TV Lines	
Lens Changeable	Yes, CS Mount	
Support DC IRIS	Yes	
IO	2 in / 2 out	
Sensitivity	0.05 lux	
Video Out	1	
Microphone	Built-in	
Audio Out	1	
Power Supply	DC 12V, 1A	
Ethernet	10/ 100 Base-T	
Network Protocol	HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, DDNS, UPnP	
Wireless	-----	802.11b/g
WEP	64/ 128 bit	
Event Trigger	Motion Detection, Sensor In	
Trigger Actions	Send Email, Send to FTP, Save to SD Card, Digital Out	
Video Resolution	NTSC: 720x480, 704x480, 352x240, 176x120 PAL: 720x576, 704x576, 352x288, 176x144	
Video Adjust	Brightness, Contrast, Saturation, Hue	
CCD Setting	AES, BLC, AGC, Day/ Night	
Image Snapshot	Yes	
Full Screen Monitoring	Yes	
Compression Format	MPEG-4/ MJPEG	
Pre/ Post Alarm	Yes, configurable	
Security	Password protection	
Firmware Upgrade	HTTP mode, can be upgraded remotely	
Simultaneous Connection	Up to 10	
Audio	Yes, 2-way	
Recording Trigger	Motion Detection, Sensor In, IP Check, Network Dis-connect	
Video Format	AVI, JPEG	
Video Playback	Yes	
Delete Files	Yes	
IR Cut Filter	Optional	
Dimensions	58mm (W) x 65mm (L) x 131.5mm (D)	